## SEMI ROTARY HAND PUMPS



MODEL NO	<b>SUCTION &amp; DELIVERY</b>	APPROX CAPACITY	NO. OF DOUBLE
	BRANCHES	IN L.P.H	STROKE PER MIN
SRH-0	½ " (15 mm)	710	105
SRH-1	¾" (20 mm)	1190	100
SRH-2	1" (25 mm)	1700	90
SRH-4	1 ¼" (32 mm)	3500	80
SRH-5	1 ½ " (40 mm)	4000	70
SRH-6	1 ½ " (40 mm)	4500	<i>65</i>
SRH-7	2" (50 mm)	7900	53
SRH-8	2" (50 mm)	8810	50
SRH-9	2 ½" (65 mm)	15600	54
SRH-10	3" ( 80 mm)	18500	48

## **SALIENT FEATURES:**

- 1) Body & cover close grain cast iron
- 2) Moving parts Brass
- 3) Shaft Steel
- 4) Gland bush Gun metal
- 5) Handle Wooden

## **RANGE:**

**SIZE** : 15mm – 80mm

**CAPACITY** : 710 LPH – 19070 LPH

- ❖ These capacities of pumps given in the table are calculated and based and on a vertical lift of suction of 1 M and a vertical delivery of 1 M with full stroke at the rate stated.
- ❖ A foot valve should be fitted when suction lift is more than 2 M
- ❖ In case the liquid is to be forced more than 4 M above the pumps, vertical check valve on the delivery pipe is desirable

## Flange details :

Size:

0-5 : Have oval flanges

6-10 : Have round flanges

0-8 : Have vertical lugs and are fitted with single handle

9-10 : Have horizontal lugs and are fitted double handle.

Address: - 21/A Canning Street, Ground Floor, Kolkata - 700001 West Bengal, India
Phone No :- (033) 2230 8125
Phone No :- (033) 2262 8392
Mobile No :- +91 88779 90087
WhatsApp No :- +91 88779 90087
Email ID. :- powerpointpumps@yahoo.co.in
Website:- <u>www.industrialpumpsindia.com/</u>